

電磁閥 / 選用表

型號	閥類種類							本體型式			*A, B 配管口尺寸及有效斷面積 mm ² (Cv 值)								閥體 寬度 (mm)	瓦特數 W (DC)	(*) 使用壓力範圍 MPa	型錄 頁次
	3 口 2 位置		5 口 2 位置		5 口 3 位置			直配管型	連座型		M3	M5	1/8"	1/4"	3/8"	1/2"	3/4"	1"				
	常閉型	常開型	單動型	複動型	中間關閉	中間通氣	中間排氣															
MVSC-220	●	●	●		●	●	●	●	●				18 (1.00)	18 (1.00)					22	2	0.2~0.8	1-5
MVSC-260			●		●	●	●	●						18 (1.00)					26	2	0.2~0.8	1-10
MVSC-300	●	●	●		●	●	●	●							35 (1.94)				30	2	0.2~0.8	1-13
MVSC-460	●	●	●		●	●	●	●								50 (2.78)			30	2	0.2~0.8	1-17
MVSC1-150			●					●	●			3.8 (0.21)							15	0.95	0.15~0.8	1-22
MVSC1-180	●	●	●		●	●	●	●					12 (0.67)						18	0.95	0.15~0.8	1-24
MVSC1-220	●	●	●		●	●	●	●	●				18 (1.00)	18 (1.00)					22	0.95	0.2~0.8	1-28
MVSD2-180			●		●	●	●	●					12 (0.67)						18	0.95	0.15~0.8	1-33
MVSE-260			●		●	●	●	●						18 (1.00)					26	2	0.2~1.2	1-37
MVSE-300			●		●	●	●	●							35 (1.94)				30	2	0.2~1.2	1-40
MVSE-500			●					●								41 (2.28)			30	2	0.2~1.2	1-43
MVSE-510			●					●								65 (3.61)			68	10	0.2~0.7	1-45
MVSE-600			●					●									115 (6.39)	135 (7.5)	68	10	0.2~0.7	1-47
MVSE2-300	●	●	●		●		●	●						19.8 (1.1)					30	3	0.12~1	1-49
MVSI-260			●		●	●	●		●					22 (1.22)					35	2	0.2~0.7	1-52
MVSI-450			●						●					27 (1.5)					45	2	0.2~0.7	1-54
MVSI-510			●						●							65 (3.61)			68	10	0.2~0.7	1-59
MVSN-220			●					●					18 (1.00)	18 (1.00)					22	2	0.2~0.7	1-61
MVSN-300			●		●	●	●	●						35 (1.94)					30	2	0.2~0.8	1-63
MVSN2-300			●		●			●						19.8 (1.1)					30	3	0.15~1	1-66
MVSP-156			●		●	●	●	●	●				11 (0.61)						15	0.95	0.15~0.7	1-68
MVSP-188			●		●	●	●	●	●					15 (0.83)					18	0.95	0.15~0.7	1-73
MVSY-100			●		●	●	●	●	●			4.5 (0.25)							10	0.55	0.2~0.8	1-77
MVSY-156			●		●	●	●	●	●				11 (0.61)						15	0.55	0.15~0.7	1-81
MVSY-188			●		●	●	●	●	●					15 (0.83)					18	0.55	0.15~0.7	1-87
MVSV-220	●	●						●					6.2 (0.34)						22	7→3	-1.01~0.7	1-92
MVDA-80	●								●			0.612 (0.034)							8	0.5	0~0.8	1-94
MVDA-120	●							●				2.184 (0.121)							12	0.8	0~0.8	1-96
MVDC-220	●							●					0.8 (0.044)						22	2	0~0.7	1-98
MVDC-300	●							●					4.4 (0.244)	4.6 (0.25)					29.6	7→3	-1.01~1	1-100
MVDY-100	●								●			0.28 (0.016)							10	0.55	0~0.9	1-102

● 2 口 2 位置及 3 口 2 位置常閉型。

* 有效斷面積及使用壓力範圍為 5 口 2 位置之值。